can-am®

McGINTY Tractors

www.mcgintytractors.com

		OUTLANDER PRO HD5 T	OUTLANDER PRO XU HD5 T / HD7 T		OUTLANDER PRO XU HD7 T ABS	OUTLANDER MAX PRO XU HD7 T
COLOR OPTIONS		Sandstone	Sandstone		Sandstone	Sandstone
ENGINES		HD5	HD5	HD7	HD7	HD7
	Type	40 hp (29.8 kW) / 50.2 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	40 hp (29.8 kW) / 50.2 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	50 hp (36.8 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	50 hp (36.8 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	50 hp (36.8 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter
	Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
	Transmission	pDrive primary CVT with work calibration Extra low L / H / N / R / P	pDrive primary CVT with work calibration Extra low L / H / N / R / P		pDrive primary CVT with work calibration Extra low L / H / N / R / P	pDrive primary CVT with work calibration Extra low L / H / N / R / P
	Drive Train	Selectable 2WD / 4WD with Visco-Lok† auto-locking front differential	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential		Selectable 2WD / 4WD / Lock 4WD with BTC (Brake traction Control)	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
	Driving Assistance	Speed limiter	Intelligent Engine Braking (iEB™)	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter
	Power Steering		Tri-Mode Dynamic Power Steering (DPS)		Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel	Double A-arm 9.75 in. (24.8 cm) travel		Double A-arm 9.75 in. (24.8 cm) travel	Double A-arm 9.75 in. (24.8 cm) travel
	Front Shocks	Twin Tube	Twin Tube		Twin Tube	Twin Tube
	Rear Suspension	Double A-arm 10.25 in. (26 cm) travel	Double A-arm 10.25 in. (26 cm) travel		Double A-arm 10.25 in. (26 cm) travel	Double A-arm 10.25 in. (26 cm) travel
	Rear Shocks	Twin Tube	Twin Tube		Twin Tube	Twin Tube
TIRES / WHEELS	Front & Rear Tires	6-ply rating 26 x 8/10 x 12 in.	XPS Trail King, 6-ply rating, 26 x 8/10 x 12 in.		XPS Trail King, 6-ply rating, 26 x 8/10 x 12 in.	XPS Trail King, 6-ply rating, 26 x 8/10 x 12 in.
	Wheels	12 in. Steel	12 in. cast aluminum		12 in. cast aluminum	12 in. cast aluminum
BRAKES	Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers		Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers
	Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	Single 214 mm disc brake with hydraulic twin-piston caliper		Single 214 mm disc brake with hydraulic twin-piston caliper	Single 214 mm disc brake with hydraulic twin-piston caliper
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	370.1kg	400.5 kg		400.5 kg	426.4 kg
	L x W x H	93 x 47.6 x 57 in. (236 x 120.9 x 144.8 cm)	93 x 48.2 x 57 in. (236 x 122.4 x 144.8 cm)		93 x 48.2 x 57 in. (236 x 122.4 x 144.8 cm)	101 x 48.8 x 57 in. (256.5 x 124 x 144.8 cm)
	Wheelbase	53 in. (134.5 cm)	53 in. (134.5 cm)		53 in. (134.5 cm)	60.4 in. (153.5 cm)
	Ground Clearance	13 in. (33 cm)	13 in. (33 cm)		13 in. (33 cm)	13 in. (33 cm)
	Seat Height	38.6 in. (98 cm)	38.6 in. (98 cm)		38.6 in. (98 cm)	38.6 in. (98 cm)
	Rack Capacity	Front: 54.4 kg / Rear: 109 kg	Front: 54.4 kg / Rear: 109 kg		Front: 54.4 kg / Rear: 109 kg	Front: 54.4 kg / Rear: 109 kg
	Storage Capacity	34 L	34 L		34 L	34 L
	Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes	830 kg trailer with brakes / 394 kg trailer without brakes		830 kg trailer with brakes / 394 kg trailer without brakes	830 kg trailer with brakes / 394 kg trailer without brakes
	Bed Capacity	N/A	N/A		N/A	N/A
	Fuel Capacity	19.5 L	19.5 L		19.5 L	19.5 L
FEATURES	Gauge	4.5 in. digital display	4.5 in. digital display		4.5 in. digital display	4.5 in. digital display
	Magneto	420-W	500-W		500-W	500-W
	Instrumentation	N/A	Phone charger with 1xUSB-A and 1xUSB-C outputs		Phone charger with 1xUSB-A and 1xUSB-C outputs	Phone charger with 1xUSB-A and 1xUSB-C outputs
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)		RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights and tail lights LED signature	LED headlights and tail lights LED signature		LED headlights and tail lights LED signature	LED headlights and tail lights LED signature
	Winch		Can-Am HD3500 (1,588 kg) winch with synthetic cable		Can-Am HD3500 (1,588 kg) winch with synthetic cable	Can-Am HD3500 (1,588 kg) winch with synthetic cable
	Seat	Standard	Standard		Standard	Removable passenger seat
	Handlebar	Standard	Standard		Standard	Standard
	Protection	Heavy Duty front bumper Rear bumper HMWPE front and rear A-Arm protection (5 mm) Full skid plate	Heavy Duty front bumper Rear bumper HMWPE front and rear A-Arm protection (5 mm) Full skid plate		Heavy Duty front bumper Rear bumper HMWPE front and rear A-Arm protection (5 mm) Full skid plate	Heavy Duty front bumper Rear bumper HMWPE front and rear A-Arm protection (5 mm) Full skid plate
	Hitch Type	2 in. hitch with tow ball	2 in. hitch with tow ball		2 in. hitch with tow ball	2 in. Rear hitch and tow ball

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
All above vehicles include a 2-year BRP limited warranty.

		OUTLANDER MAX PRO XU HD10 / HD11 T		OUTLANDER X MR	OUTLANDER XT 1000 T ABS
COLOR OPTIONS		Granite Grey	Dolomite Grey	Granite Grey	Fiery Red Metallic
ENGINES		HD10	HD11	700	1000
	Type	82 hp (60.3 kW)/ 89.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter, radiator cooling fan of 80W & 150 cc	101 hp (74.3 KW)/ 93.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled,, catalytic converter, high flow radiator cooling fan of 120W & 500 cc	50 hp (36.8 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled with strategically positioned engine air intake	82 hp (60.3 kW)/ 89.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter, radiator cooling fan of 80W & 150 cc
	Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
	Transmission	pDrive primary CVT with work calibration Extra low L / H / N / R / P		pDrive primary CVT with strategically positioned air intake and exhaust Extra low L / H / N / R / P	pDrive primary CVT L / H / N / R / P
	Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential		Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential	Selectable 2WD / 4WD with BTC (Brake traction Control)
	Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter		Work / Standard / Sport modes Intelligent Engine Braking (iEB™)	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)
	Power Steering	Tri-Mode Dynamic Power Steering (DPS)		Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	Front Suspension	Arched Double A-arm 10.8 in. (27.4 cm) travel		Double A-arm 9 in. (22.9 cm) travel	Arched Double A-arm 10.8 in. (27.4 cm) travel
	Front Shocks	Twin tube		Twin Tube	Twin Tube
	Rear Suspension	Arched Double A-arm 12 in. (30.5 cm) travel		Double A-arm 9.75 in. (24.8 cm) travel	Arched Double A-arm 12 in. (30.5 cm) travel
	Rear Shocks	Twin tube		Twin Tube	Twin Tube
TIRES / WHEELS	Front & Rear Tires	XPS Trail King, 6-ply rating, 27 x 8/10 x 14 in.		XPS Swamp King 28 x 8/10 x 14 in.	XPS Trail King 2 - 26 x 8/10 x 14
	Wheels	14 in. cast aluminum		14 in. Aluminum	14 in. Aluminum
BRAKES	Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers		Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers
	Rear	Single 214 mm disc brake with hydraulic twin-piston caliper		Single 214 mm disc brake with hydraulic twin-piston caliper	Single 214 mm disc brake with hydraulic twin-piston caliper
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	453 kg		397.3 kg	442 kg
	L x W x H	102 x 49.2 x 57 in. (259 x 125 x 144.8 cm)		89.6 x 48.2 x 49 in. (227.6 x 122.4 x 124.5 cm)	90.2 x 49.2. x 47.9 in. (229.1 x 125 x 122 cm)
	Wheelbase	60.8 in. (154.4 cm)		53 in. (134.5 cm)	52.8 in. (134.2 cm)
	Ground Clearance	12.5 in (31.75 cm)		13 in. (33 cm)	12 in. (30.5 cm)
	Seat Height	38.3 in. (97.3 cm)		38.6 in. (98 cm)	37.8 in. (96 cm)
	Rack Capacity	Front: 54.4 kg / Rear: 109 kg		Front: NA / Rear: 109 kg	Front: 54.4 kg / Rear: 109 kg
	Storage Capacity	40 L		3.8 L	40 L
	Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes		830 kg trailer with brakes / 394 kg trailer without brakes	830 kg trailer with brakes / 394 kg trailer without brakes
	Bed Capacity	N/A		N/A	N/A
	Fuel Capacity	19.5 L		19.5 L	19.5 L
FEATURES	Gauge	7.6 in. digital display		4.5 in. digital display	10.25 in. Touch display
	Magneto	650-W		500-W	650-W
	Instrumentation	Phone storage & USB-C charger		Phone charger with 1xUSB-A and 1xUSB-C outputs	Phone storage & USB-C charger
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)		RF Digitally Encoded Security System (D.E.S.S.™) with tether	RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights and tail lights LED signature		LED headlights and tail lights	LED headlights and tail lights LED signature
	Winch	Can-Am HD3500 (1,588 kg) winch with synthetic cable			Can-Am HD3500 (1,588 kg) winch with synthetic cable
	Seat	Removable passenger seat		Standard	Standard
	Handlebar	Standard		Standard	Standard
	Protection	Heavy Duty front and rear bumpers HMWPE front and rear A-Arm protection (5 mm) Full skid plate		Front bumper X mr footpegs Full skid plate	Full skid plate Heavy Duty front and rear bumpers Handguards
	Hitch Type	2 in. Rear hitch and tow ball		2 in. hitch receiver	2 in. hitch with tow ball

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
All above vehicles include a 2-year BRP limited warranty.

		OUTLANDER DPS 500 T ABS / 700 T ABS		OUTLANDER MAX DPS 500/700 T ABS		OUTLANDER MAX XT 700 T ABS
COLOR OPTIONS		Granite Grey		Granite Grey		Dolomite Grey
ENGINES		500	700	500	700	700
	Type	40 hp (29.8 kW) / 50.2 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	50 hp (36.8 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	40 hp (29.8 kW) / 50.2 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	50 hp (36.8 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	50 hp (36.8 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter
	Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
	Transmission	pDrive primary CVT L / H / N / R / P		pDrive primary CVT L / H / N / R / P		pDrive primary CVT L / H / N / R / P
	Drive Train	Selectable 2WD / 4WD with BTC (Brake traction Control)		Selectable 2WD / 4WD with BTC (Brake traction Control)		Selectable 2WD / 4WD with BTC (Brake traction Control)
	Driving Assistance	N/A	Work / Standard / Sport modes	N/A	Work / Standard / Sport modes	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)
	Power Steering	Tri-Mode Dynamic Power Steering (DPS)		Tri-Mode Dynamic Power Steering (DPS)		Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel		Double A-arm 9.75 in. (24.8 cm) travel		Double A-arm 9.75 in. (24.8 cm) travel
	Front Shocks	Twin Tube		Twin Tube		Twin Tube
	Rear Suspension	Double A-arm 10.25 in. (26 cm) travel		Double A-arm 10.25 in. (26 cm) travel		Double A-arm 10.25 in. (26 cm) travel
	Rear Shocks	Twin Tube		Twin Tube		Twin Tube
TIRES / WHEELS	Front & Rear Tires	25 x 8/10 x 12 in.		25 x 8/10 x 12 in.		Trail Force 26 x 8/10 x 14 in.
	Wheels	12 in. aluminum		12 in. aluminum		14 in. Aluminum
BRAKES	Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers		Dual 214 mm disc brakes with hydraulic twin-piston calipers		Dual 214 mm disc brakes with hydraulic twin-piston calipers
	Rear	Single 214 mm disc brake with hydraulic twin-piston caliper		Single 214 mm disc brake with hydraulic twin-piston caliper		Single 214 mm disc brake with hydraulic twin-piston caliper
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	348.2 kg		364.1 kg		413.1 kg
	L x W x H	89.2 x 48.2 x 55.9 in. (226.6 x 122.4 x 142 cm)		97.2 x 48.2 x 55.9 in. (249.9 x 122.4 x 142 cm)		100.2 x 48.8 x 56.9 in. (254.5 x 124 x 144.5 cm)
	Wheelbase	53 in. (134.5 cm)		60.4 in. (153.5 cm)		60.4 in. (153.5 cm)
	Ground Clearance	12 in. (30.5 cm)		12 in. (30.5 cm)		12.5 in. (31.8 cm)
	Seat Height	38 in. (96.7 cm)		38.6 in. (98 cm)		38.6 in. (98 cm)
	Rack Capacity	Front: 54.4 kg / Rear: 109 kg		Front: 54.4 kg / Rear: 109 kg		Front: 54.4 kg / Rear: 109 kg
	Storage Capacity	34 L		34 L		34 L
	Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes		830 kg trailer with brakes / 394 kg trailer without brakes		830 kg trailer with brakes / 394 kg trailer without brakes
	Bed Capacity	N/A		N/A		N/A
	Fuel Capacity	19.5 L		19.5 L		19.5 L
FEATURES	Gauge	4.5 in. digital display		4.5 in. digital display		4.5 in. digital display
	Magneto	500-W		500-W		500-W
	Instrumentation	N/A		N/A		Phone charger with 1xUSB-A and 1xUSB-C outputs
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)		RF Digitally Encoded Security System (D.E.S.S.™)		RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights and tail lights LED signature		LED headlights and tail lights LED signature		LED headlights and tail lights LED signature
	Winch					Can-Am HD3500 (1,588 kg) winch with synthetic cable
	Seat	Standard		Removable passenger seat		Removable passenger seat
	Handlebar	Standard		Standard		Standard
	Protection	Full skid plate		Full skid plate		Front and rear bumpers Full skid plate
	Hitch Type	2 in. hitch with tow ball		2 in. hitch with tow ball		2 in. hitch with tow ball

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
All above vehicles include a 2-year BRP limited warranty.

		OUTLANDER MAX XT 1000 T ABS	OUTLANDER XT-P 1000R T ABS/ XT-P 1000R T ABS - WITH SAS		OUTLANDER X MR 1000R
COLOR OPTIONS		Fiery Red Metallic	Dusty Navy		Loft Green Satin
ENGINES		1000	1000R T ABS	1000R T ABS with SAS	1000R
	Type	82 hp (60.3 kW)/ 89.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter, radiator cooling fan of 80W & 150 cc	101 hp (74.3 KW)/ 93.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter high flow radiator cooling fan of 120W & 500 cc		101 hp (74.3 KW)/ 93.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled with strategically positioned engine air intake High flow radiator cooling fan of 120W & 500 cc
	Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
	Transmission	pDrive primary CVT L / H / N / R / P	pDrive primary CVT with specific calibration L / H / N / R / P		pDrive primary CVT with strategically positioned air intake and exhaust & specific calibration Extra low L / H / N / R / P
	Drive Train	Selectable 2WD / 4WD with BTC (Brake traction Control)	Selectable 2WD / 4WD / Lock 4WD with BTC (Brake traction Control)		Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential
	Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)		Work / Standard / Sport modes Intelligent Engine Braking (iEB™)
	Power Steering	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)		Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	Front Suspension	Arched Double A-arm 10.8 in. (27.4 cm) travel	Arched Double A-arm with sway bar 10.8 in. (27.4 cm) travel		Arched Double A-arm 7.5 in. (19 cm) travel
	Front Shocks	Twin Tube	Piggyback FOX Podium QS3 Gas shocks	KYB shocks with Smart-Shox Technology	SHOWA Internal Floating Pistons (IFP) Shocks
	Rear Suspension	Arched Double A-arm 12 in. (30.5 cm) travel	Arched Double A-arm 12 in. (30.5 cm) travel		Arched Double A-arm 10.2 in. (25.9 cm) travel
	Rear Shocks	Twin Tube	Piggyback FOX Podium QS3 Gas shocks	KYB shocks with Smart-Shox Technology	SHOWA Internal Floating Pistons (IFP) Shocks
TIRES / WHEELS	Front & Rear Tires	XPS Trail King 2 - 26 x 8/10 x 14 in.	XPS Trail King 2 - 27 x 8/10 x 14 in.		XPS Swamp King XL 30 x 9/10 x 14 in.
	Wheels	14 in. Aluminum	14 in. Aluminum beadlock		14 in. Aluminum
BRAKES	Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers		Dual 214 mm disc brakes with hydraulic twin-piston calipers
	Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	Single 214 mm disc brake with hydraulic twin-piston caliper		Dual 214 mm disc brakes with hydraulic twin-piston calipers
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	453 kg	442 kg		474 kg
	L x W x H	101.9 x 49.2 x 55.9 in. (258.9 x 125 x 142 cm)	93.9 x 49.2 x 55.9 in. (238.5 x 125 x 142 cm)		95.6 x 49.7 x 54.2 in. (242.9 x 126.2 x 137.6 cm)
	Wheelbase	60.8 in. (154.4 cm)	52.8 in. (134.2 cm)		52.8 in. (134.2 cm)
	Ground Clearance	12 in. (30.5 cm)	12 in. (30.5 cm)		13.2 in. (33.5 cm)
	Seat Height	37.8 in. (96 cm)	37.8 in. (96 cm)		37.8 in. (96 cm)
	Rack Capacity	Front: 54.4 kg / Rear: 109 kg	Front: 54.4 kg / Rear: 109 kg		Front: NA / Rear: 109 kg
	Storage Capacity	40 L	40 L		3.8 L
	Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes	830 kg trailer with brakes / 394 kg trailer without brakes		830 kg trailer with brakes / 394 kg trailer without brakes
	Bed Capacity	N/A	N/A		N/A
	Fuel Capacity	19.5 L	19.5 L		19.5 L
FEATURES	Gauge	10.25 in. Touch display	7.6 in. digital display	10.25 in. Touch display	7.6 in. digital display
	Magneto	650-W	650-W		650-W
	Instrumentation	Phone storage & USB-C charger	Phone storage & USB-C charger		Phone storage & USB-C charger
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)		RF Digitally Encoded Security System (D.E.S.S.™) with tether
	Lighting	LED headlights and tail lights LED signature	LED headlights and tail lights LED signature		LED headlights and tail lights LED signature
	Winch	Can-Am HD3500 (1,588 kg) winch with synthetic cable	Can-Am HD3500 (1,588 kg) winch with synthetic cable		3,500 lb (1,588 kg) bumper mounted winch with synthetic cable
	Seat	Removable passenger seat	Special Edition seat (color, stiching and material)		Special Edition seat (color, stiching and material)
	Handlebar	Standard	Aluminum taper-profile handlebar with sport handguards		Aluminum tapered-profile handlebar with J-Hook, mud handgrip, mud strap and 1 in. riser
	Protection	Full skid plate Heavy Duty front and rear bumpers Handguards	Full skid plate Heavy Duty front and rear bumpers Handguards		Full skid plate MUD front bumper with winch mount Heavy Duty rear bumper Aluminum pegs (driver footrest)
	Hitch Type	2 in. hitch with tow ball	2 in. hitch with tow ball		2 in. hitch receiver

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
All above vehicles include a 2-year BRP limited warranty.

		OUTLANDER MAX X MR 1000R	OUTLANDER MAX DPS 1000 T/ 1000R T ABS		OUTLANDER MAX XT-P 1000R T ABS/ 1000R T ABS - WITH SAS	
COLOR OPTIONS		Loft Green Satin	Granite Grey		Dusty Navy	
ENGINES		1000R	1000	1000R	1000R	
	Type	101 hp (74.3 KW)/ 93.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled with strategically positioned engine air intake High flow radiator cooling fan of 120W & 500 cc	82 hp (60.3 kW)/ 89.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter, radiator cooling fan of 80W & 150 cc	101 hp (74.3 KW)/ 93.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter, high flow radiator cooling fan of 120W & 500 cc	101 hp (74.3 KW)/ 93.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter, high flow radiator cooling fan of 120W & 500 cc	
	Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
	Transmission	pDrive primary CVT with strategically positioned air intake and exhaust & specific calibration Extra low L / H / N / R / P	pDrive primary CVT L / H / N / R / P	pDrive primary CVT with specific calibration L / H / N / R / P	pDrive primary CVT with specific calibration L / H / N / R / P	
	Drive Train	Selectable 2WD / 4WD / Lock 4WD with Visco-4Lok front differential	Selectable 2WD / 4WD with BTC (Brake traction Control)		Selectable 2WD / 4WD / Lock 4WD with BTC (Brake traction Control)	
	Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)		Work / Standard / Sport modes Intelligent Engine Braking (iEB™)	
	Power Steering	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)		Tri-Mode Dynamic Power Steering (DPS)	
SUSPENSIONS	Front Suspension	Arched Double A-arm 7.5 in. (19 cm) travel	Arched Double A-arm 10.8 in. (27.4 cm) travel		Arched Double A-arm with sway bar 10.8 in. (27.4 cm) travel	
	Front Shocks	SHOWA Internal Floating Pistons (IFP) Shocks	Twin Tube		Piggyback FOX Podium QS3 Gas shocks	KYB shocks with Smart-Shox Technology
	Rear Suspension	Arched Double A-arm 10.2 in. (25.9 cm) travel	Arched Double A-arm 12 in. (30.5 cm) travel		Arched Double A-arm 12 in. (30.5 cm) travel	
	Rear Shocks	SHOWA Internal Floating Pistons (IFP) Shocks	Twin Tube		Piggyback FOX Podium QS3 Gas shocks	KYB shocks with Smart-Shox Technology
TIRES / WHEELS	Front & Rear Tires	XPS Swamp King XL 30 x 9/10 x 14 in.	26 x 8/10 x 14 in.		XPS Trail King 2 - 27 x 8/10 x 14 in.	
	Wheels	14 in. Aluminum	14 in. Aluminum		14 in. Aluminum beadlock	
BRAKES	Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers		Dual 214 mm disc brakes with hydraulic twin-piston calipers	
	Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Single 214 mm disc brake with hydraulic twin-piston caliper		Single 214 mm disc brake with hydraulic twin-piston caliper	
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	486 kg	439 kg		453 kg	
	L x W x H	102.2 x 47.6 x 54 in. (259.5 x 120.9 x 137.1 cm)	99.1 x 49.2 x 55.9 in. (251.7 x 125 x 142 cm)		101.9 x 49.2 x 55.9 in. (258.9 x 125 x 142 cm)	
	Wheelbase	60.8 in. (154.4 cm)	60.8 in. (154.4 cm)		60.8 in. (154.4 cm)	
	Ground Clearance	13.5 in. (34.3 cm)	12 in. (30.5 cm)		12 in. (30.5 cm)	
	Seat Height	37.8 in. (96 cm)	37.8 in. (96 cm)		37.8 in. (96 cm)	
	Rack Capacity	Front: NA / Rear: 109 kg	Front: 54.4 kg / Rear: 109 kg		Front: 54.4 kg / Rear: 109 kg	
	Storage Capacity	3.8 L	40 L		40 L	
	Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes	830 kg trailer with brakes / 394 kg trailer without brakes		830 kg trailer with brakes / 394 kg trailer without brakes	
	Bed Capacity	N/A	N/A		N/A	
	Fuel Capacity	19.5 L	19.5 L		19.5 L	
FEATURES	Gauge	7.6 in. digital display	7.6 in. digital display		7.6 in. digital display	10.25 in. Touch display
	Magneto	650-W	650-W		650-W	
	Instrumentation	Phone storage & USB-C charger	Phone storage		Phone storage & USB-C charger	
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with tether	RF Digitally Encoded Security System (D.E.S.S.™)		RF Digitally Encoded Security System (D.E.S.S.™)	
	Lighting	LED headlights and tail lights LED signature	LED headlights and tail lights		LED headlights and tail lights LED signature	
	Winch	3,500 lb (1,588 kg) bumper mounted winch with synthetic cable			Can-Am HD3500 (1,588 kg) winch with synthetic cable	
	Seat	Special edition 1-up seat with storage box	Removable passenger seat		Special Edition seat (color, stiching and material) with removable passenger seat	
	Handlebar	Aluminum tapered-profile handlebar with J-Hook, mud handgrip, mud strap and 1 in. riser	Standard		Aluminum taper-profile handlebar with sport handguards	
	Protection	Full skid plate MUD front bumper with winch mount Heavy Duty rear bumper Aluminum pegs (driver footrest)	Full skid plate		Full skid plate Heavy Duty front and rear bumpers Handguards	
	Hitch Type	2 in. hitch receiver	2 in. hitch with tow ball		2 in. hitch with tow ball	

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
All above vehicles include a 2-year BRP limited warranty.

		OUTLANDER MAX LIMITED 1000R T ABS WITH SAS	OUTLANDER 6X6 DPS 700 T	OUTLANDER MAX 6X6 DPS 700 T
COLOR OPTIONS		Stealth Black	Granite Grey	Granite Grey
ENGINES		1000R	700	700
	Type	101 hp (74.3 KW)/ 93.5 Nm, Rotax 999 cc V-twin, DOHC, liquid cooled, catalytic converter, high flow radiator cooling fan of 120W & 500 cc	50 hp (37.3 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter	50 hp (37.3 kW) / 55.6 Nm, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled, catalytic converter
	Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
	Transmission	pDrive primary CVT with specific calibration L / H / N / R / P	pDrive primary CVT with work calibration Extra low L / H / N / R / P	pDrive primary CVT with work calibration Extra low L / H / N / R / P
	Drive Train	Selectable 2WD / 4WD / Lock 4WD with BTC (Brake traction Control)	Selectable 4WD / 6WD with Visco-Lok QE front differential	Selectable 4WD / 6WD with Visco-Lok QE front differential
	Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™)	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter
	Power Steering	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	Front Suspension	Arched Double A-arm with sway bar 10.8 in. (27.4 cm) travel	Double A-arm 9.8 in. (24.8 cm) travel	Double A-arm 9.8 in. (24.8 cm) travel
	Front Shocks	KYB shocks with Smart-Shox Technology	Oil shocks (REC calibration)	Oil shocks (REC calibration)
	Rear Suspension	Arched Double A-arm 12 in. (30.5 cm) travel	Double A-arm 9.7 in. (24.7 cm) travel	Double A-arm 9.7 in. (24.7 cm) travel
	Rear Shocks	KYB shocks with Smart-Shox Technology	Oil shocks (REC calibration)	Oil shocks (REC calibration)
TIRES / WHEELS	Front & Rear Tires	XPS Trail King 2 - 27 x 8/10 x 14 in.	XPS Trail King - 26 x 8/10 x 12 in.	XPS Trail King - 26 x 8/10 x 12 in.
	Wheels	14 in. Aluminum	12 in. Steel	12 in. Steel
BRAKES	Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers
	Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	453 kg	514 kg	558 kg
	L x W x H	101.9 x 49.2 x 55.9 in. (258.9 x 125 x 142 cm)	116.3 x 48.5 x 56.5 in. (295.3 x 124 x 143.5 cm)	124.3 x 48.5 x 56.5 in. (315.7 x x 124 x 143.5 cm)
	Wheelbase	60.8 in. (154.4 cm)	85.7 in. (217.6 cm)	93.3 in (237 cm)
	Ground Clearance	12 in. (30.5 cm)	12 in. (30.5 cm)	12 in. (30.5 cm)
	Seat Height	37.8 in. (96 cm)	36.8 in. (93.4 cm)	36.8 in. (93.4 cm)
	Rack Capacity	Front: 54.4 kg / Rear: 109 kg	Front: 54.4 kg	Front: 54.4 kg
	Storage Capacity	40 L	Front cargo: 30 L Rear cargo: 220 L Total : 250 L	Front cargo: 30 L Rear cargo: 220 L Total : 250 L
	Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes	1,125 kg trailer with brakes / 500 kg trailer without brakes	1,125 kg trailer with brakes / 500 kg trailer without brakes
	Bed Capacity	N/A	454 kg	454 kg
	Fuel Capacity	19.5 L	19.5 L	19.5 L
FEATURES	Gauge	10.25 in. Touch display	4.5 in. digital display	4.5 in. digital display
	Magneto	650-W	500-W	500-W
	Instrumentation	Phone storage & USB-A charger	Glove box	Glove box
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights and tail lights LED signature	LED headlights and tail lights LED signature	LED headlights and tail lights LED signature
	Winch	Can-Am HD3500 (1,588 kg) winch with synthetic cable		
	Seat	Special Edition seat (color, stiching and material) with removable passenger seat	Standard	Removable passenger seat
	Handlebar	Standard	Standard	Standard
	Protection	Full skid plate Heavy Duty front and rear bumpers Handguards	Full skid plate	Full skid plate
	Hitch Type	2 in. hitch with tow ball	2 in. Rear hitch and tow ball	2 in. Rear hitch and tow ball

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
All above vehicles include a 2-year BRP limited warranty.

		OUTLANDER 6X6 DPS 1000 T	OUTLANDER MAX 6X6 DPS 1000 T	OUTLANDER 6X6 BACKCOUNTRY 1000R T	OUTLANDER MAX 6X6 BACKCOUNTRY 1000R T
COLOR OPTIONS		Granite Grey	Granite Grey	Stealth Black	Stealth Black
ENGINES		1000	1000	1000R	1000R
	Type	82 hp (60.3 kW) / 89.5 Nm, Rotax® 999 cc V-twin, DOHC, liquid cooled, catalytic converter, high flow radiator cooling fan of 120W & 500 cc	82 hp (60.3 kW) / 89.5 Nm, Rotax® 999 cc V-twin, DOHC, liquid cooled, catalytic converter, high flow radiator cooling fan of 120W & 500 cc	101 hp (74.3 KW) / 93.5 Nm, Rotax® 999 cc V-twin, DOHC, liquid cooled, catalytic converter, high flow radiator cooling fan of 120W & 500 cc	101 hp (74.3 KW) / 93.5 Nm, Rotax® 999 cc V-twin, DOHC, liquid cooled, catalytic converter, high flow radiator cooling fan of 120W & 500 cc
	Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
	Transmission	pDrive primary CVT with work calibration Extra low L / H / N / R / P	pDrive primary CVT with work calibration Extra low L / H / N / R / P	pDrive primary CVT with work calibration Extra low L / H / N / R / P	pDrive primary CVT with work calibration Extra low L / H / N / R / P
	Drive Train	Selectable 4WD / 6WD with Visco-Lok QE front differential	Selectable 4WD / 6WD with Visco-Lok QE front differential	Selectable 4WD / 6WD / Lock 6WD with Visco-6Lok front differential	Selectable 4WD / 6WD / Lock 6WD with Visco-6Lok front differential
	Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter
	Power Steering	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	**Front Suspension**	Arched Double A-arm 10 in. (25.2 cm) travel	Arched Double A-arm 10 in. (25.2 cm) travel	Arched Double A-arm with sway bar 7.5 in. (19.5 cm) travel	Arched Double A-arm with sway bar 7.5 in. (19.5 cm) travel
	Front Shocks	Oil shocks (REC calibration)	Oil shocks (REC calibration)	SHOWA Internal Floating Pistons (IFP) Shocks	SHOWA Internal Floating Pistons (IFP) Shocks
	Rear Suspension	Arched Double A-arm 9.8 in. (24.8 cm) travel	Arched Double A-arm 9.8 in. (24.8 cm) travel	Arched Double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel	Arched Double A-arm with sway bar on middle axle 9 in. (22.9 cm) travel
	Rear Shocks	Oil shocks (REC calibration)	Oil shocks (REC calibration)	SHOWA Internal Floating Pistons (IFP) Shocks	SHOWA Internal Floating Pistons (IFP) Shocks
TIRES / WHEELS	**Front & Rear Tires**	XPS Trail King - 28 x 8/10 x 14 in.	XPS Trail King - 28 x 8/10 x 14 in.	XPS Iron Force - 30 x 9 x 14 in.	XPS Iron Force - 30 x 9 x 14 in.
	Wheels	14 in. Aluminum	14 in. Aluminum	14 in. Aluminum beadlock	14 in. Aluminum beadlock
BRAKES	**Front**	Oversized Dual 252 mm disc brakes with hydraulic twin-piston calipers	Oversized Dual 252 mm disc brakes with hydraulic twin-piston calipers	Oversized Dual 252 mm disc brakes with hydraulic twin-piston calipers	Oversized Dual 252 mm disc brakes with hydraulic twin-piston calipers
	Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers
DIMENSIONS / CAPACITIES	**Estimated Dry Weight***	581 kg	631 kg	623 kg	659 kg
	L x W x H	116.3 x 49.3 x 56.5 in. (295.3 x 125.2 x 143.5 cm)	124.3 X 49.3 X 56.5 in. (315.7 x 125.2 x 143.5 cm)	119.1 x 49.7 x 59 in. (302.5 x 126.1 x 149.9 cm)	127.2 X 49.7 X 59 in. (323 x 126.1 x 149.9 cm)
	Wheelbase	85.7 in. (217.6 cm)	93.3 in (237 cm)	85.7 in. (217.6 cm)	93.3 in (237 cm)
	Ground Clearance	12 in. (30.5 cm)	12 in. (30.5 cm)	13 in. (33 cm)	13 in. (33 cm)
	Seat Height	36.8 in. (93.4 cm)	36.8 in. (93.4 cm)	37.8 in. (96 cm)	37.8 in. (96 cm)
	Rack Capacity	Front: 54.4 kg	Front: 54.4 kg	Front: 54.4 kg	Front: 54.4 kg
	Storage Capacity	Front cargo: 30 L Rear cargo: 220 L Rear undercargo: 25 L Total : 275 L	Front cargo: 30 L Rear cargo: 220 L Rear undercargo: 25 L Total : 275 L	Front cargo: 30 L Rear cargo: 220 L Rear undercargo: 25 L Total : 275 L	Front cargo: 30 L Rear cargo: 220 L Rear undercargo: 25 L Total : 275 L
	Towing Capacity	1,125 kg trailer with brakes / 750 kg trailer without brakes	1,125 kg trailer with brakes / 750 kg trailer without brakes	1,125 kg trailer with brakes / 750 kg trailer without brakes	1,125 kg trailer with brakes / 750 kg trailer without brakes
	Bed Capacity	454 kg	454 kg	454 kg	454 kg
	Fuel Capacity	19.5 L	19.5 L	19.5 L	19.5 L
FEATURES	**Gauge**	7.6 in. digital display	7.6 in. digital display	7.6 in. digital display	7.6 in. digital display
	Magneto	650-W	650-W	650-W	650-W
	Instrumentation	Phone storage	Phone storage	Phone storage & USB-C charger	Phone storage & USB-C charger
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights and tail lights LED signature	LED headlights and tail lights LED signature	LED headlights and tail lights LED signature	LED headlights and tail lights LED signature
	Winch			Can-Am HD3500 (1,588 kg) winch with synthetic cable	Can-Am HD3500 (1,588 kg) winch with synthetic cable
	Seat	Standard	Removable passenger seat	Special Edition	Special edition seat with removable passenger seat
	Handlebar	Standard	Standard	Aluminum with riser and handguards	Aluminum with riser and handguards
	Protection	Full skid plate	Full skid plate	Heavy Duty front bumper Full skid plate Footwell protectors Front & rear a-arms protectors Handguards	Heavy Duty front bumper Full skid plate Footwell protectors Front & rear a-arms protectors Handguards
	Hitch Type	2 in. Rear hitch and tow ball	2 in. Rear hitch and tow ball	2 in. Rear hitch and tow ball	2 in. Rear hitch and tow ball

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
**Smart-Shox was developed in conjunction with Tractive Industries, a market leader in the suspension industry.
All above vehicles include a 2-year BRP limited warranty.

		OUTLANDER ELECTRIC T	OUTLANDER MAX ELECTRIC T
COLOR OPTIONS		White	White
MOTORS	Type	Electric	Electric
		47 hp (35kW) / 72 Nm, ROTAX® E-POWER, Liquid-cooled	47 hp (35kW) / 72 Nm, ROTAX® E-POWER, Liquid-cooled
	Power	Peak: 47 hp (35 kW) Continuous: 27 hp (20 kW)	Peak: 47 hp (35 kW) Continuous: 27 hp (20 kW)
	Torque Motor	Peak: 72 Nm Continuous: 28 Nm	Peak: 72 Nm Continuous: 28 Nm
	Top Speed	High gear: 37 mph (60 km/h) Low gear: 28 mph (45 km/h)	High gear: 37 mph (60 km/h) Low gear: 28 mph (45 km/h)
BATTERY	Battery Type	Integrated, Lithium-ion	Integrated, Lithium-ion
	Battery Operating Temperature Range	From -20°C to 40°C	From -20°C to 40°C
	Battery Capacity	8.9 kWh	8.9 kWh
	Cooling System	Liquid-cooled : Battery, inverter and on-board charger (charging cable not included, sold as accessory) Integrated AC heater for charging at low temperature	Liquid-cooled : Battery, inverter and on-board charger (charging cable not included, sold as accessory) Integrated AC heater for charging at low temperature
	Estimated Range (when fully charged)	Tested in accordance with WMTC*: 50 miles (80 km) Average utility range*: 31 miles (50 km)	Tested in accordance with WMTC*: 50 miles (80 km) Average utility range*: 31 miles (50 km)
	Regenerative braking	Regen braking with 3 levels adjustments	Regen braking with 3 levels adjustments
	Charger	On-board charger 6.6 kW Level 2 (compatible with level 1 charging) - charging cable not included, sold as accessory	On-board charger 6.6 kW Level 2 (compatible with level 1 charging) - charging cable not included, sold as accessory
	Connector Type	Type 2 IEC 62196 with integrated LED light	Type 2 IEC 62196 with integrated LED light
	Charging Time Level 2 (240 V)	50 min (20 - 80 %) 1 hour 30 min (0 - 100%)	50 min (20 - 80 %) 1 hour 30 min (0 - 100%)
	Charging Time Level 1 (120 V)	3 hours 10 min (20 - 80%) 5 hours 15 min (0 - 100%)	3 hours 10 min (20 - 80%) 5 hours 15 min (0 - 100%)
DRIVETRAIN	Transmission	L / N / H / P Reverse activated via start button	L / N / H / P Reverse activated via start button
	Drive Train	Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential	Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential
	Driving Assistance	Work / Standard / Sport modes Speed limiter	Work / Standard / Sport modes Speed limiter
	Power Steering	Tri-Mode Dynamic Power Steering (DPS)	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel	Double A-arm 9.75 in. (24.8 cm) travel
	Front Shocks	Twin tube	Twin tube
	Rear Suspension	Double A-arm 10.25 in. (26 cm) travel	Double A-arm 10.25 in. (26 cm) travel
	Rear Shocks	Twin tube	Twin tube
TIRES / WHEELS	Front & Rear Tires	XPS Recon Force 26 x 8/10 x 14 in.	XPS Recon Force 26 x 8/10 x 14 in.
	Wheels	14 in. cast aluminum	14 in. cast aluminum
BRAKES	Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	Dual 214 mm disc brakes with hydraulic twin-piston calipers
	Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	Single 214 mm disc brake with hydraulic twin-piston caliper
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	402 kg	420 kg
	L x W x H	89.9 x 48.1 x 49.6 in. (228.3 x 122.2 x 126 cm)	98 x 48.1 x 56 in. (249 x 122.2 x 142.2 cm)
	Wheelbase	53 in. (134.5 cm)	60.7 in. (154.2 cm)
	Ground Clearance	12 in. (30.5 cm)	12 in. (30.5 cm)
	Seat Height	38 in. (96.7 cm)	38.6 in. (98 cm)
	Rack Capacity	Front: 54.4 kg / Rear: 109 kg	Front: 54.4 kg / Rear: 109 kg
	Storage Capacity	34 L	34 L
	Towing Capacity	830 kg trailer with brakes / 394 kg trailer without brakes	830 kg trailer with brakes / 394 kg trailer without brakes
	Bed Capacity		
FEATURES	Gauge	5 in. colored display	5 in. colored display
	Magneto	Continuous 500W (at all speed including at idle)	Continuous 500W (at all speed including at idle)
	Instrumentation	Phone charger with 1xUSB-A and 1xUSB-C outputs	Phone charger with 1xUSB-A and 1xUSB-C outputs
	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	RF Digitally Encoded Security System (D.E.S.S.™)
	Lighting	LED headlights and tail lights LED signature LED POD light	LED headlights and tail lights LED signature LED POD light
	Winch		
	Seat	Standard	Removable passenger seat
	Handlebar	Standard	Standard
	Protection	Front and rear bumpers Full skid plate	Front and rear bumpers Full skid plate
	Hitch Type	2 in. hitch receiver with towball	2 in. hitch receiver with towball

† Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners.
*Base model dry weight shown.
Battery: 5 years (12,427 miles / 20,000 km limit), Vehicle: 2-year BRP Limited warranty

		YOUTH RENEGADE X XC
COLOR OPTIONS		Orange Crush
ENGINES	Type	110 EFI
		112 cc 4-stroke single cylinder, air cooled
	Fuel Delivery System	Electronic Fuel Injection (EFI) with built-in throttle limiter
	Transmission	CVT F / N / R
	Drive Train	Chain driven / 2WD Electric starting system
	Driving Assistance	N/A
	Power Steering	N/A
SUSPENSIONS	Front Suspension	Double A-arm / 5.5 in. (14 cm) travel
	Front Shocks	Gas with piggyback reservoirs
	Rear Suspension	Swingarm / 6 in. (15.2 cm) travel
	Rear Shocks	Gas
TIRES / WHEELS	Front & Rear Tires	Front: 19 x 7 x 8 in. Rear: 18 x 9.5 x 8 in.
	Wheels	8 in. steel
BRAKES	Front	Dual drum brakes
	Rear	Single drum brake
DIMENSIONS / CAPACITIES	Estimated Dry Weight*	140 kg
	L x W x H	60.6 x 42 x 38.6 in. (154 x 108 x 98 cm)
	Wheelbase	41 in. (105 cm)
	Ground Clearance	8.3 in. (21.1 cm) under frame / 4.5 in. (11.4 cm) under rear axle
	Seat Height	28 in. (71 cm)
	Rack Capacity	N/A
	Storage Capacity	N/A
	Towing Capacity	N/A
	Bed Capacity	N/A
	Fuel Capacity	6 L
FEATURES	Gauge	Neutral, reverse, fuel level & check engine lights
	Magneto	N/A
	Instrumentation	N/A
	Ignition	Mechanical key
	Lighting	Halogen running headlights
	Winch	N/A
	Seat	Standard
	Handlebar	Sport handguards Ergonomy & controls sized for 10 years old and up
	Protection	Front bumper
	Hitch Type	N/A

This vehicle includes a 2-year BRP limited warranty.

CANAMOFFROAD.COM

BRP